

TDB-ACC-NO: NNRD440152

DISCLOSURE TITLE: Flux Guide/Tunnel Valve Structure With
Conducting
Contiguous Junction

PUBLICATION-DATA: IBM technical Disclosure Bulletin, December
2000, UK

ISSUE NUMBER: 440

PAGE NUMBER: 2198

PUBLICATION-DATE: December 1, 2000 (20001201)

CROSS REFERENCE: 0374-4353-0-440-2198

DISCLOSURE TEXT:

Disclosed is a new flux guide/tunnel valve structure which achieves conducting contiguous junction between the flux guide and the tunnel valve sensor. The conducting contiguous junction will provide higher flux coupling efficiency compared to the prior art insulating contiguous junction. In addition, the new structure provides straight side walls for the front flux guide implying better track width definition.

The process sequence/steps for the new structure is:

1. Deposit bottom ferromagnetic shield.
2. Deposit insulation, flux guide, and insulation.
3. Pattern flux guide (etch flux guide only), deposit hard bias and insulation over the hard bias. The structure at this point is shown in Fig. A.
4. Pattern tunnel valve, etch flux guide and insulation down to shield. The structure is shown in Fig. B.

5. Deposit **tunnel valve** with free layer at bottom.
 6. Pattern **tunnel valve**, and deposit insulation/hard bias/insulation. The structure is shown in Fig. C.
 7. Deposit top ferromagnetic shield.
- The shields make electrical contact only to **tunnel valve**.

SECURITY: Use, copying and distribution of this data is subject to the restrictions in the Agreement For IBM TDB Database and Related Computer Databases. Unpublished - all rights reserved under the Copyright Laws of the United States. Contains confidential commercial information of IBM exempt from FOIA disclosure per 5 U.S.C. 552(b)(4) and protected under the Trade Secrets Act, 18 U.S.C. 1905.

COPYRIGHT STATEMENT: The text of this article is Copyrighted (c) IBM Corporation 2000. All rights reserved.